

## New generation wastes & traps with integrated seals

WASHBASIN TRAPS							
	DESIGNATION	Ø	WATER SEAL	INLET TUBE HEIGHT ADJUSTMENT MM	REF.	PACK.	PACK.
	<b>EASYPHON, Trap with integrated seals</b>						
	BM21S, 32/32 Easyphon	32	50	39-98	<b>0201284 *</b>	S1	40
	C2921, BM21S with ø32 wall outlet pipe, 239 mm	32	50	39-98	<b>0202073 *</b>	S1	40
	<b>BMT02, BM21S with co-injected spacesaving rear pipe, 250 mm</b>	32	50	39-98 + 56	<b>0202135 *</b>	S1	20
	BM24S, 32/40 Easyphon	40	50	39-98	<b>0201285 *</b>	S1	40
	C2924, BM24S with ø 40 wall outlet pipe, 239 mm	40	50	39-98	<b>0202074 *</b>	S1	30
	BM217, Easyphon with co-injected waste, with plug	32	50	50-100 ; 0-50	<b>0202123</b>	S1	25
	C2950, BM217 with ø 32 wall outlet pipe, 239 mm	32	50	50-100 ; 0-50	<b>0202122</b>	S1	13
	BM19, 32/32 Easyphon with washing-machine connection	32	50	83-128	<b>0201302 *</b>	S1	20
	C2919, BM19 with ø 32 wall outlet pipe, 239 mm	32	50	83-128	<b>0201308</b>	S1	45

SINK TRAPS							
	DESIGNATION	Ø	WATER SEAL	INLET TUBE HEIGHT ADJUSTMENT MM	REF.	PACK.	PACK.
	<b>EASYPHON, Trap with integrated seals</b>						
	BM55S, 40/40 Easyphon	40	50	39-98	<b>0224287 *</b>	S1	40
	CE52S, BM55S with ø 40 mm wall outlet pipe, 239 mm	40	50	39-98	<b>0202075 *</b>	S1	40
	BM53, 40/40 Easyphon with washing-machine connection	40	50	83-128	<b>0224360 *</b>	S1	20
	CE53, BM53 with ø 40 wall outlet pipe, 239 mm	40	50	83-128	<b>0224408 *</b>	S1	20

BATHTUB DRAINAGES WITH CABLE							
	DESIGNATION	WATER SEAL	CABLE AND OVERFLOW TUBE LENGTH	REF.	PACK.	PACK.	
	<b>EASYBAIN, co-injection technology cable bathtub drainage</b> Trap with integrated seals, very compact, high flow rate (70 l/min which is 30% more than the one of the EN requirements), self-cleaning, with a 5° directional outlet, factory pre-assembled and adjustable 650mm overflow, without cutting. Attractively-designed hand wheels with excellent grip.						
	<b>EASYBAIN Stick, hand wheel and plug in chrome-plated brass</b>						
	EB08S, 650mm with D40/50 elbow connector	50	650 mm	<b>0203619 *</b>	B1	13	
	EB08, 650mm cable	50	650 mm	<b>0203613 *</b>	B1	14	
	EB18S, 1m with D40/50 elbow connector	50	1 m	<b>0203620 *</b>	B1	13	
	EB18, 1m cable	50	1 m	<b>0203614 *</b>	B1	14	
	<b>EASYBAIN Wave, hand wheel and plug in chrome-plated ABS</b>						
	EB07S, 650 mm with D40/50 elbow connector	50	650 mm	<b>0203617 *</b>	S1	25	
	EB07, 650 mm	50	650 mm	<b>0203611 *</b>	S1	25	
	EB17S, 1 m with D40/50 elbow connector	50	1m	<b>0203618 *</b>	S1	20	
	EB17, 1 m	50	1 m	<b>0203612 *</b>	S1	20	

BATHTUB TRAPS							
	DESIGNATION	WATER SEAL	OVERFLOW TUBE LENGTH	REF.	PACK.	PACK.	
	<b>EASYCLIC, foot-controlled waste and overflow head in chrome-plated brass</b> Co-injected trap						
	EB602, 650 mm overflow tube	50	650 mm	<b>0203543</b>	S1	20	
	EB652, 1 m overflow tube	50	1 m	<b>0203560</b>	S1	20	

\* approved products

Credits photos : Nicoll / Document non contractuel

## New generation wastes & traps with integrated seals

**NEW**



**New generation wastes & traps with integrated seals**

Easyphton and Easybain use the new co-injection technology : the TPE seals and the PP trap body are injected simultaneously.

A Patented technology that delivers exceptional benefits

- Reliable and safe to use thanks to integrated seals that are surprisingly elastic and durable
- Perfect and long-lasting seals :
  - The connections are 100% watertight : the seals are always correctly positioned
- A complete and NF-EN 274-certified range to equip washbasins, sinks and bathtubs



**EASYPHON**  
Co-injection technology

Washbasin, sink



Easy to install  
«Adjust, tighten, done»



Quick and easy maintenance  
«Remove, rinse, reassemble»



Space-saving solution with the washbasin rear pipe



Washbasin co-injected waste



**Benefits :**

- Ultra-fast and long-lasting installation
- No need for additional work on the site after installation
- A profitable plumbing, guaranteed

**EASYBAIN**  
Co-injection technology

Bathtub



Watertightness ensured by the co-injected seals



**Benefits :**

- Connecting the trap to the pipe is made easier
- Simple and fast installation
- An outstanding trap in terms of flow rate and compactness



Double-rotating 360° trap




5° directional outlet

70l/mn



The flow rate is 30% higher than the NF-EN 274 requirements, the best performance on the market. Flush-effect flow that makes it possible to clear out deposits and provide optimal drainage over time



+ 20 cm

The pre-assembled overflow can be extended or retracted by 20 cm (on the 650 mm version).



Choice of design for hand wheels and plugs

The most compact trap on the market : 108 mm only, including the NF-EN required 50 mm water seal height.



108 mm