

# Connecto<sup>®</sup> drainage channel with B125 L130 polyamide grating

## Building

**NEW**



Nicoll's range of drainage channels has expanded and now includes the CAN10BN drainage channel, complete with polyamide grating. This class B125 product is the ideal solution for use at garage entrances and other traffic areas.

### Advantages:

- Anticorrosion: polyamide grating reinforced with fibreglass
- Robust and light: can withstand wheel loads
- Attractive: black mesh design. UV-resistant
- High hydraulic capacity
- Safe: complies with PRM accessibility requirements, screw-mounted grating
- Easy to install
- Watertight system



# Connecto® drainage channel with B125 L130 polyamide grating

## Building



|  | NAME   |  | REFERENCE      | PACK.   |
|--|--|--|----------------|---|
|  | <b>1 m PP drainage channel with 2 screw-down B125 polyamide gratings</b> |  | <b>CAN10BN</b> | Sold in 32-metre pallets<br><b>only</b> , charged per 1-metre section |
|  | <b>32-metre pallet</b> (delivery unit)                                   |  | <b>PAN10BN</b> |   |
|  | <b>End or side stopend outlet</b> , diameter 100                         |  | <b>NAT177N</b> | 10  |
|  | <b>End or side stopend outlet</b> , diameter 110                         |  | <b>NAV177N</b> | 10  |
|  | <b>Tapping for vertical outlet</b> , diameter 100                        |  | <b>STDR10</b>  | 10  |
|  | <b>Tapping for vertical outlet</b> , diameter 110                        |  | <b>SVDR10</b>  | 10  |
|  |  |  |                |   |

### USE

The new CAN10BN drainage channel is used to collect run-off water. It is primarily designed for applications requiring class B125 resistance as a minimum, such as garage entrances, private car parks, pavements, multi-storey car parks and pedestrian areas with light vehicle access.

### ADVANTAGES

**Connecto® body:** Ultra-light, modular system that makes it easy to handle and install, with the option of vertical and lateral tapping.

**Durable:** the grating is resistant to the main chemical agents (grit, chlorine, salt, etc.)



**Complies with PRM accessibility requirements**

**Robust:** resistance class B125


**Watertight system:** complies with the technical guide for installation conditions

**Attractive:** black with overhauled mesh design

**Optimized grating expansion:** grating sections screwed down with sufficient space for proper expansion

**Anticorrosion:** the grating is made from polyamide reinforced with fibreglass, offering exceptional resistance to corrosion. No risk of rust.

### TECHNICAL CHARACTERISTICS

- Drainage channel body with black polypropylene rabbets
- Anti-UV treated polyamide grating
- Resistance class B125 (NF EN 1433)
- Complies with PRM accessibility requirements 
- Absorption surface area: 411 cm<sup>2</sup>/ml

